## POINT WENONAH PART OF GOVT. LOT NO. 1 SEC. 32 & GOVT. LOT NO. 3 SEC. 29 Ö TOWNSHIP - TIBN, RFE-ARENAC COUNTY, MICHIGAN STANDISH ₹ ... ALL DIMENSIONS. ARE IN FERT & DECIMALS .THERE OF ALL WATER FRONT LOTS EXTEND TO WATERS EDGE. ONE INCH . BO FEET \$ 87° - 30 E 710 S. & LINE SEC. 29 S. 1º 15' W 597.15 VACANT LAND POINT OF DECINNING 13 65 65 67 68 N89 44'E 781.3 WILLOW DRIVE P. W. S. 44 PE POINT WENONAH SUB. No 2. 172 2.5 126 CERTIFICATE OF MUNICIPAL APPROVAL DEDICATION ₹ 173 KNOW ALL MEN BY THESE PRESENTS, That Merbele Corporation, a Michigan corporation, by Margaret L. Berry its President, and Elisabeth M. Osbeck its Secretary, as proprietor, have caused the land embraced in the armered plat to be surveyed, laid out and platted to be known as FOTH WENORMH MO. 3 Part Of Covt. Lot No. 1 Sec. 32 & Govt. Lot No. 3-Sec. 29 Standish Tomakip—TLEN, EDS-Frence County, Michigan-and that the streets and alleys—as shown on said plat have been previously dedicated to the use of the lot owners only. , B 30. 127 8 ั้ง เก ш 12.8 Ruth Milne (C 5 175 Z8 129 â (PRIVAT Marbele Corporation 3314 Bronson Blwd. Kalamazoo, Michigan CERTIFICATE OF APPROVAL BY COUNTY BOARD 4777 Ú 130 oʻ 176 Signed and Sealed in the Presence of ROAD 131 Richard C. Jaka Margard J. Burposident Margaret L. Berry Avis Black Z Kenneth Osbeck Elizabeth M. Osbeck O Point ₹ C. Black 73 178 Ü ACKNOWLEDGMENT Ì & Non-History d. 650 6 E 933 Michael Pavelka 9 180 COUNTY TREASURER'S CERTIFICATE RELATING TO TAXES 102 0 P 3 2 3 181 Office of County Treasurer, Arenac .... County 111 ,09 ,09

Clark

This certificate does not apply to taxes, if any, now in process of collection by township, city or village collecting officers.

CERTIFICATE OF APPROVAL BY BOARD OF

Said point being 4025.48 feet \$ 2026.48 W from the North 1/4 corner of said Section 29;

This, plat has been examined and was approved on the Arenac County Board of Ross Countsioners.

Dass Verrin

Ross Perrin (C)

Michael mulko (Manhor)
Highael Pavellin (Manhor)

(Cheirmen)

(County Presquer)

My Commission expires Sept. 22. 1945 Robert J. Byrne
Notary Public Kent Gev Missigen
"Corporation has no corporate seal"

SEC.

M

25

18 N

182

3 183

102

102

185

COPY

Recorded this 29 R day of Supple A. D., 1966 at 10 O'clock

s Office Grenze County. no hint We

A.M. in Liber in Page 38,

Ux

17 20 30 W 448.4

az

020020 C

N89 44 W-20.0

ofPlats

Chie Black
Register of DentOPIGINAL ON FILE

t Parery cartify this copy is a true copy of map or plet forwarded the Register of Deeds for recording Strandard St. (1866).
Fi. ED IN 1057: OF TREASURY THE STANDARD AND APPROVED.

Date Derenher 28, 1966 Quison Sum ALLISON GREEN
STATE THEASURER
By Kichard E. James
Richard E. Lomax - Plat Examiner 110

10%

108

107

106

## DESCRIPTION OF LAND PLATTED

The land embraced in the annexed plat of Point Wenomah No. 3 a subdivision of part of Government Lot No. 1, Section 32, and a part of Government Lot No. 3, Section 32, and a part of Government Lot No. 3, Section 32, and a part of Government Lot No. 3, Section 32, and a part of Government Lot No. 3, Section 29, all in Standish Township, TEN, RSE, Arenac Gounty, Michigan is described as follows:—Commencing at a point on the North and South 1 line of Section 29 intersects said North and South 1 line, thence S R7930'
East 710 feet on said S 1/8 line, thence Such 1915'
Yest S97.15 feet for the point of beginning, said point being the SW corner of the Chase. J. Sturmen's Sub. as recorded on page by, Libre 1 of plate, Arenac County Records, and also the NW corner of Point Memonah Subdivision No. 2 as recorded on page by, Libre 2 of plate, Arenac County records; themse from said point of beginning S 1200' 30' Seast 933 feet on the Meet Line of existing Point Load, thence N 87'30' Meet 102 feet, thence N 120' 30' Seast 933 feet, thence S 127'30' East 102 feet to the point of beginning. Said land is divided into 15 lots numbered from 172 to 186 inclusive.

## SURVEYOR'S CERTIFICATE

I hereby certify that the plat hereon delineated is a correct one and that permanent metal monuments consisting of iron rods at least one half inch in diameter and thirty-six inches in length encased in concrete cylinder at least four inches in diameter and thirty-six inches have been placed at all points marked thus "o" as thereon shown at all angles in the boundary of the plat at the intersections of the streets, and at the intersections of the lines of streets, and at the intersections of the lines of streets with the boundaries of the plat as shown as said plat.

Prepared and Drafted by the following the lines of the lines of the lines of the plat as shown as said plat.

Registered Professional Engineer No. 6971